

EcoFlood 130 LED flood light

The EcoFlood is a UK designed & manufactured LED Flood light with a 130,000 hour (L70) rated life and an industry leading 10 year Warranty. Available in floor standing or wall mounted version.



interLED

Technical Specifications

- Commercial & Industrial outdoor & indoor lighting, architectural lighting
- Mounting height typically 5-15m
- 9,900 lumens
- 130,000 hours (L70) & 80,000 hours (L80) rated life
- Colour temperature ; 5000k, 4000k, 3000k
- UK made
- Length: 255mm - Width: 380mm - Height: 225mm
- Weight kg: 8.6
- Beam Optics 30°, 40°, 64°, 90° or 110° integrated reflectors
- 90° Anti-Glare Optic has frosted lens
- Cast aluminium body designed for longevity through thermal efficiency
- Toughened glass front cover
- Operating temp: -20°+ 45°
- Standard finish in Silver
- Azko Nobel 'Interpon' powder coat
- Other RAL colours available to suit your branding or colour scheme
- MeanWell driver (IP67)
- Lighting designs carried out with DIALux software
- Call to discuss further options
- 10 years warranty



Performance. The EcoFlood 130 Watt is designed to withstand the harshest outdoor environments using ultra reliable CREE® LED chips and industry best Meanwell power supplies. This 130 Watt version delivers 9,900 lumens in varying beam optics. **Environment.** The EcoFlood is suitable for outdoor use in architectural or industrial projects, sports centres, & retail. It has also been used extensively internally and externally in theological buildings. **Options.** The EcoFlood is available in 2 versions ;

* EcoFloor – Floor Standing

* EcoWall – Wall & ceiling mounting

For both variants there are options on beam angles, colour temperatures and colour finishes

- INT/ECOW/130/5K/G90
- INT/ECOF/130/5K/G90
- INT/ECOW/130/5K/64
- INT/ECOF/130/5K/64
- INT/ECOW/130/5K/40