

# HiCloud Mini HIGH BAY LED LIGHT

A compact version of the popular HiCloud suitable for a variety of applications where a robust fitting is required with a small form factor. Offers all the benefits of the standard version.



## interLED

### Technical Specifications

- Warehousing, Industrial, Sports Halls and Commercial Buildings
- Mounting heights 3-10M
- 50,000 hours rated life L70
- 5,000K Colour temperature
- ECA Qualifying (Enhanced Capital Allowance)
- Operating Temp. -40°C to +50°C
- 0.3m flex (other lengths and plugs optional)
- 90° Optics available on request
- Length: 264mm - Width: 264mm - Height: 121mm
- Robust cast aluminium construction with durable powder coated finish
- Weight kg: 3.2
- 120° tempered glass standard
- Stainless steel screws
- Five years warranty
- Hook mounting options available
- Driver - 60,000 hour lifespan using quality Meanwell LED driver
- High quality aluminium heatsink that provides efficient heat dissipation
- Nichia SMD LED's
- 150lm/watt
- IK Rating 08 / 10



**Performance.** The HiCloud mini benefits from Nichia LED chips and Meanwell driver to perform at 125 lumens per Watt. **Environment.** Suitable for use in dusty and damp industrial environments or where a robust fitting is essential. The reduced size and lower outputs are ideal in small rooms with reduced mounting heights and closer spacing between the lights. **Options.** Lumen packages from 6,250 to 11,700 lm are available. Standard diffuser is a 120° tempered glass cover but with an option for a 90° optic.

- INT-LED-HCM-70 - HiCloud Mini 70w 5,000k 8,250lm 120° IP65
- INT-LED-HCM-90 - HiCloud Mini 90w 5,000k 11,700lm 120° IP65