

VP/NCR Single Batten

LED Non-Corrosive or Vapour Proof battens


Direct like for like retro-fit replacements for 'Single' fluorescent battens offering improved light output & 50% energy reduction



interLED

Technical Specifications

- Industrial buildings, Manufacturing facilities, Cold stores, Kitchens
- Mounting height typically 2.4 - 7m
- 1,400 - 3,500 lumens
- 50,000 hour rated life (L70)
- Colour temperature; 4000k or 5000k
- CRI>80
- 100 lumens per Watt
- 2' (664mm), 4' (1274mm), 5' (1574mm)
- IK08 impact resistant
- IP65
- Tough & Durable Polycarbonate body & Diffuser
- Operating temp. range -30~+50°C
- Tridonic driver
- Standard finish in Grey with frosted diffuser
- Microwave detection option
- 3 hour Emergency battery back-up option
- ECA Qualifying (Enhanced Capital Allowance)
- 5 year warranty
- Call to discuss further options
- Lighting designs carried out with DIALux software



Performance. This 'Single' version is available in 2, 4 and 5ft versions, replacing the equivalent single tube fluorescent fitting. At least a 50% energy reduction with improved light output is achievable, when compared to a traditional T8 fluorescent luminaire. **Environment.** Commonly used in industrial applications where chemicals used in manufacturing may cause corrosion to metal fixtures, or where there is moisture in the atmosphere, like cooking areas, canteens and kitchens. **Options.** Microwave presence detectors can be built in to the fitting for increased energy savings in areas of limited occupation. There is also a 3 hour emergency option available. For like for like replacement of fluorescent fittings with Twin tubes, we have a 'Twin' version of this luminaire.

- INT/2S/NCR/4K
- INT/4S/NCR/4K
- INT/5S/NCR/4K
- INT/5S/NCR/4K/MW
- INT/4S/NCR/4K/MWEM