

interLED Pro LED Ceiling Panel

Our best selling, mid range panel incorporating high quality power supplies for longevity & reliability.



interLED

Technical Specifications

- Offices, showrooms, reception areas, clerical and medical rooms
- Mounting height from 2 - 3m
- 3,500 lumen
- 50,000 hour rated life
- CCT: 4000k standard
- CRI>80
- 40W
- Epistar LED Chips
- For modular 600x600mm suspended ceiling
- Length: 595mm x Width 595mm x Height 40mm
- High Grade 6063 Aluminium Frame
- Weight kg : 2.5
- Opal (PS)
- Efficacy 87.5Lm/W
- Operating range -20° ~ +50°
- Power factor > 0.95
- DALI/1-10v/DSI/Switch-Dim option
- CE marked
- Tridonic driver as standard
- Five year warranty

Performance. The Pro LED Panel has become our most popular selling panel for customers upgrading commercial lighting. This panel is ideally suited to standard ceiling heights up to 3 meters, delivering 500-700 lux when installed at 2.4 m centres. **Environment.** Ideally suited to general office environments with a 600x600mm modular lay-in exposed ceiling grid. It can also be installed to plasterboard ceilings using the surface mount kit supplied separately. **Options.** For dimming requirements the Pro panel can be equipped with a Tridonic 'Multi Dim' power supply which incorporates DALI/1-10v or SwitchDim technologies. The 3 Hour Emergency option includes a built-in indicator for ease of installation. A surface mount kit is also available for ceilings without a modular lay-in grid.

- INT/6x6/PRO/40/840
- INT/6x6/PRO/40/840/DIM
- INT/6x6/PRO/30/840/EM
- INT/6x6/PRO/30/840/DIM/EM
- INT/12x3/PRO/30/840/ Standard / Dim / EM